

- 5 LITRE GRAVITY FEED TANK.
- 30 METRES PUMPING HEAD.
- 110 L/HR FLOW RATES.

DP30-S

• INTELLIGENT OVERLOAD PROTECTION.



The DP30-S is a low profile yet powerful piston pump design for use with dairy case installation. With pumping heads of up to 30 metres and flow rates of up to 110 litres/hour which makes this pump suitable for both single and multiple case installation. Its Ultra Low height also means that it can be used for dairy cases where height is a restriction.

The DP30 and Mini DP30 are extremely powerful diaphragms pumps designed for use with dairy case installations. With pumping heads of up to 30 metres and flow rates of up to 270 litres/hour, making these units suitable for both single and multiple case application.

Other standard features include, high level alarm contacts rated at 2A 230v AC to control the AC unit if the pump is unable to remove the condensate and **Intelligent Overload Protection** that prevents damage to the pump motor if the suction/discharge pipes are restricted or the pump has been mis-applied.

TECHNICAL SPECIFICATION								
	DP30-S	DP30	MINI DP30					
ELECTRICAL	110v versio	on available on request						
Voltage	230v 50Hz	230v 50Hz	230v 50Hz					
Power	37W	240W	240W					
PERFORMANCE								
Pumping Head	30 M	30 M	30 M					
Tank Capacity	5 Litres	13 Litres	6 Litres					
Inlet Connection	1/2" OD	50mm OD	50mm OD					
Outlet Connection	15mm OD	15mm ID	15mm ID					
PHYSICAL								
Height	60mm	95mm	95mm					
Length	465mm	660mm	420mm					
Width	205mm	300mm	300mm					

	PUM	PING H	IEAD		
1m	10m	15m	20m	25m	
272 l/hr	230 l/hr	219 l/hr	207 l/hr	195 l/hr	PC
	но	RIZONTAL	RUN		ö
200m	35m	10m	Х	Х	

	PUM	PING H	IEAD	
1m	10m	15m	20m	25m
110 l/hr	60 l/hr	50 l/hr	45 l/hr	40 l/hr
	но	RIZONTAL	RUN	
90m	60m	45m	30m	X

13 LITRE GRAVITY FEED TANK.

- 30 METRES PUMPING HEAD.
- 270L/HR FLOW RATES.
- INTELLIGENT OVERLOAD PROTECTION.

• 6 LITRE GRAVITY FEED TANK.

- 30 METRES PUMPING HEAD.
- 270 L/HR FLOW RATE.
- INTELLIGENT OVERLOAD PROTECTION.





DAIRYCASE